





Specification

Product Name		LED Down Light		Image	
Model No.		BM-DL-3WA			
Optical characteristic	LED source	Bridgelux		Photometric data	
	LED type	1W High power			
	CCT	6000-6500K			
	LED quantity	3PCS			
	Cover Type	PMMA			
	Luminous efficiency	90LM/W			
	Luminous Flux	>270LM			
	CRI	Ra ≥ 75			
	Beam angle	30° 60°			
Electricity characteristic	Input voltage/Current	AC85V-277V/ 0.018A-0.060A		LUX	
	Frequency	50-60Hz			
	Output voltage	9-12V			
	Output current	300ma ± 3%			
	Power	3.6W			
	LED Power	3W			
	Power efficiency	≥ 85%			
	Power factor	>0.7			
	Dimmable	Optional			
Other characteristic	Surface temperature	55°C(environment temperature31°C)		Structure	
	Operating temperature	-35°C-- +55°C			
	Installing method	Screw			
	Work humidity	5%-95%RH			
	Storage temperature	-40°C-- +65°C			
	Equivalent Incandescent lamp	25W			
	IP rate	IP64			
	LED lifespan	>40000h			
	Casing material	AL			
	Weight	150g			
	Size	Φ 85*45mm			
	Opening Size	Φ 75mm			
	Box size	1pcs/box 90×90×50mm			
	Carton size	100pcs/carton460×460×205mm			