

Specification

Product Name		LED Panel Light		Image	
Model No.		BM-RPL180-8W			
Optical characteristic	LED source	Epistar		Photometric data	
	LED type	SMD3528			
	CCT	6000-6500K			
	LED quantity	104PCS			
	Cover Type	PMMA			
	Luminous efficiency	80LM/W			
	Luminous Flux	640LM			
	CRI	Ra ≥ 75			
Beam angle	≥ 120°				
Electricity characteristic	Input voltage/Current	AC85V-277V/ 0.029A-0.094A		LUX	
	Frequency	50-60Hz			
	Output voltage	24-32V			
	Output current	250ma ± 3%			
	Power	8W			
	LED Power	6.5W			
	Power efficiency	≥ 85%			
	Power factor	>0.9			
Dimmable	Can choose TRIAC				
Other characteristic	Surface temperature	45℃		Structure	
	Operating temperature	-20℃ -- +40℃			
	Installing method	Embedded, Ceiling and Suspended ceiling			
	Work humidity	5%-95%RH			
	Storage temperature	-30℃ -- +65℃			
	Equivalent halogen bulb	12W			
	IP rate	IP64			
	LED lifespan	>40000h			
	Casing material	AL			
	Weight	350g			
	Size	Φ 180* Φ 165*H25mm			
	Opening Size	Φ 172mm			
	Box size	1pcs/box 235×235×55 mm			
Carton size	20pcs/carton 485×305×485mm				