





# Specification

<b>Product Name</b>		<b>LED Street Light</b>	<b>Image</b>	
<b>Model No.</b>		<b>BM-SL160A-180W</b>		
<b>Optical characteristic</b>	LED source	Bridgelux	<b>Photometric data</b>	
	LED type	40W Integrated light source		
	CCT	2700-6500K		
	LED quantity	4PCS		
	Cover Type	Glass		
	Luminous efficiency	90LM/W		
	Luminous Flux	18000LM		
	CRI	Ra ≥ 75		
Beam angle	60°			
<b>Electricity characteristic</b>	Input voltage/Current	AC85V-277V/ 0.65A-2.14A	<b>LUX</b>	
	Frequency	50-60Hz		
	Output voltage	28-36v		
	Output current	4.8A ± 3%		
	Power	180W		
	LED Power	160W		
	Power efficiency	≥ 85%		
	Power factor	>0.95		
Dimmable	NO			
<b>Other characteristic</b>	Surface temperature	55°C (environment temperature 31°C)	<b>Structure</b>	
	Operating temperature	-35°C -- +55°C		
	Installing method	Screw fixation		
	Work humidity	5%-95%RH		
	Storage temperature	-40°C -- +65°C		
	Equivalent halogen bulb	400W		
	IP rate	IP65		
	LED lifespan	>40000h		
	Casing material	AL		
	Weight	11kg		
	Size	L700*346*104 mm		
	Pole Height	10-12M		
	Pole Spacing	30-40M		
Box size	1pcs/box 750×360×12mm			