

Specification

Product Name		Fluorescent lamp			Image	
Model No.		BM-T5A058-9W				
Optical characteristic	LED source	Epistar			Photometric data	<p>Intensity(unit:cd) C0-180</p>
	LED type	SMD3528				
	CCT	6000-6500K				
	LED quantity	126PCS				
	Cover Type	Transparent	Striped	Frosted		
	Luminous efficiency	92LM/W	90LM/W	85LM/W		
	Luminous Flux	825LM	800LM	775LM		
	CRI	Ra ≥ 75				
Beam angle	≥ 120°					
Electricity characteristic	Input voltage/Current	AC85V-277V/ 0.035A-0.105A			LUX	<p>Height Avg./NadLr. E Angle:167.50deg Diameter</p>
	Frequency	50-60Hz				
	Output voltage	27-42v				
	Output current	230ma ± 3%				
	Power	8.2W				
	LED Power	7W				
	Power efficiency	≥ 85%				
	Power factor	>0.9				
Dimmable	Optional					
Other characteristic	Surface temperature	45°C (environment temperature 31°C)			Structure	<p>580 30.5 23.4</p>
	Operating temperature	-35°C -- +55°C				
	Installing method	Insert and screw				
	Work humidity	5%-95%RH				
	Storage temperature	-40°C -- +65°C				
	Equivalent halogen bulb	20W				
	IP rate	IP64				
	LED lifespan	>40000h				
	Casing material	AL				
	Weight	230g				
	Size	W23.4*H30.5*L580mm				
	Socket	G5				
	Box size	1pcs/box 36×36×620mm				
Carton size	25pcs/carton 660×210×200mm					