




Specification

Product Name		LED Bulb	Image	
Model No.		BM-120-27W		
Optical characteristic	LED source	Bridgelux	Photometric data	
	LED type	1W High power		
	CCT	6000-6500K		
	LED quantity	27PCS		
	Cover Type	PC		
	Luminous efficiency	90LM/W		
	Luminous Flux	>2850LM		
	CRI	Ra ≥ 75		
	Beam angle	180°		
Electricity characteristic	Input voltage/Current	AC85V-277V/ 0.124A-0.364A	LUX	
	Frequency	50-60Hz		
	Output voltage	81-95V		
	Output current	300ma ± 3%		
	Power	31W		
	LED Power	27W		
	Power efficiency	≥ 85%		
	Power factor	>0.9		
	Dimmable	Optional		
Other characteristic	Surface temperature	55°C (environment temperature 31°C)	Structure	暂无
	Operating temperature	-35°C -- +55°C		
	Installing method	Screw		
	Work humidity	5%-95%RH		
	Storage temperature	-40°C -- +65°C		
	Equivalent Incandescent lamp	300W		
	IP rate	IP64		
	LED lifespan	>40000h		
	Casing material	AL		
	Weight	1000g		
	Size	Φ 120*198mm		
	Socket	E26 E27		
	Box size	1pcs/box 125×125×205mm		
Carton size	8pcs/carton 255×255×415mm			