

Specification

Product Name		Fluorescent lamp			Image	
Model No.		BM-T10A058-9W				
Optical characteristic	LED source	Epistar			Photometric data	
	LED type	SMD3528				
	CCT	6000-6500K				
	LED quantity	144PCS				
	Cover Type	Transparent	Striped	Frosted		
	Luminous efficiency	92LM/W	90LM/W	85LM/W		
	Luminous Flux	925LM	900LM	875LM		
	CRI	Ra ≥ 75				
Beam angle	≥ 120°			LUX		
Input voltage/Current	AC85V-277V/ 0.036A-0.118A					
Frequency	50-60Hz					
Output voltage	36-42v					
Output current	216ma ± 3%					
Power	9.65W					
LED Power	8.3W					
Power efficiency	≥ 85%					
Power factor	>0.9					
Dimmable	Optional			Structure		
Surface temperature	45°C (environment temperature 31°C)					
Operating temperature	-35°C -- +55°C					
Installing method	Insert and screw					
Work humidity	5%-95%RH					
Storage temperature	-40°C -- +65°C					
Equivalent halogen bulb	20W					
IP rate	IP64					
LED lifespan	>40000h					
Casing material	AL					
Weight	220g					
Size	Φ 30*580mm					
Socket	G13 Rotary lamp 180°					
Box size	1pcs/box 36×36×620mm					
Carton size	25pcs/carton 630×230×220mm					